

Accessories

Memory cards, connection cables and mounting sets



Memory Cards	Item No.	Pack. Unit	Technical Data
CF memory card, 1 GB	758-879/000-000	1	Flash memory: 1 GByte Write/Read cycles max.: Single: 20 Mbytes/s (max.) / 10 Mbytes/s (max.); Dual: 40 Mbytes/s (max.) / 20 Mbytes/s (max.) MTBF: 300,000 hrs. Service life: 2,000,000 program/operating cycles Operating temperature: -40 °C ... +85 °C Storage temperature: -55 °C ... +95 °C Relative humidity (without condensation): 95 % Dimensions (mm) W x H x L: 42.8 x 36.4 x 3.3 Vibration resistance: acc. to IEC 60068-2-6
SD memory card, 2 GB	758-879/000-001	1	Memory: 2 GByte Write/Read cycles max.: 16 Mbytes/s / 22 Mbytes/s MTBF: 4,000,000 hrs. Service life: 2,000,000 program/operating cycles Operating temperature: -45 °C ... +90 °C Storage temperature: -45 °C ... +90 °C Relative humidity (without condensation): 95 % Dimensions (mm) W x H x L: 24 x 32 x 2.1 Vibration resistance: 15 G Shock resistance: 50 G (operating), 1000 G (not operating) Data transmission rate: Up to 22 Mbytes/s
MicroSD memory card, 1 GB	758-879/000-002	1	Memory: 1 GByte Write/Read cycles max.: 18 Mbytes/s / 16 Mbytes/s MTBF: 5,000,000 hrs. Service life: 2,000,000 program/operating cycles Operating temperature: -40 °C ... +85 °C Storage temperature: -40 °C ... +85 °C Relative humidity (without condensation): 95 % Dimensions (mm) W x H x L: 15 x 11 x 1 Vibration resistance: 15 G Shock resistance: 1000 G Data transmission rate: Up to 18 Mbytes/s

Connection Cables	Item No.	Pack. Unit
DVI-D cable, 3 m	758-879/000-100	1
USB A-B cable, 3 m	758-879/000-101	1

Befestigungsset (als Ersatzteil für das dem Produkt beiliegende Set)	Item No.	Pack. Unit
Mounting set for WP, CP 35	758-879/000-300	1
Mounting set for WP, CP 57	758-879/000-301	1
Mounting set for WP, CP 104	758-879/000-302	1
Mounting set for WP, CP 121	758-879/000-303	1
Mounting set for CP 150	758-879/000-304	1