Dual General Purpose Transistors

NPN/PNP Duals (Complementary)

BC846BPDW1, BC847BPDW1, BC848CPDW1 Series

These transistors are designed for general purpose amplifier applications. They are housed in the SC-88 which is designed for low power surface mount applications.


Features

- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant


MAXIMUM RATINGS

Rating	Symbol	Value	Unit
NPN			
Collector-Emitter Voltage BC846 BC847 BC848	V_{CEO}	 65 45 30	V
Collector-Base Voltage BC846 BC847 BC848	V_{CBO}	 80 50 30	V
Emitter-Base Voltage	V_{EBO}	6.0	V
Collector Current – Continuous	I_C	100	mAdc
Collector Current – Peak	I_{CM}	200	mAdc
PNP			
Collector-Emitter Voltage BC846 BC847 BC848	V_{CEO}	 −65 −45 −30	V
Collector-Base Voltage BC846 BC847 BC848	V_{CBO}	 −80 −50 −30	V
Emitter-Base Voltage	V_{EBO}	−6.0	V
Collector Current – Continuous	I_C	−100	mAdc
Collector Current – Peak	I_{CM}	−200	mAdc


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



SC-88
CASE 419B-02
STYLE 1



MARKING DIAGRAM



XX = Device Code
M = Date Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information on page 17 of this data sheet.

© Semiconductor Components Industries, LLC, 2016

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation Per Device FR-5 Board (Note 1) T_A = 25 °C Derate above 25 °C	P_D	 380 250 3.0	 mW mW/°C mW/°C
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	328	°C/W
Junction and Storage Temperature	T_J, T_{stg}	−55 to +150	°C

1. FR-5 = 1.0 x 0.75 x 0.062 in.

ELECTRICAL CHARACTERISTICS (NPN) (T_A = 25 °C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector-Emitter Breakdown Voltage (I_C = 10 mA) BC846 BC847 BC848	$V_{(BR)CEO}$	 65 45 30	 – – –	 – – –	V
Collector-Emitter Breakdown Voltage (I_C = 10 μA, V_{EB} = 0) BC846 BC847B BC848	$V_{(BR)CES}$	 80 50 30	 – – –	 – – –	V
Collector-Base Breakdown Voltage (I_C = 10 μA) BC846 BC847 BC848	$V_{(BR)CBO}$	 80 50 30	 – – –	 – – –	V
Emitter-Base Breakdown Voltage (I_E = 1.0 μA) BC846 BC847 BC848	$V_{(BR)EBO}$	 6.0 6.0 6.0	 – – –	 – – –	V
Collector Cutoff Current (V_{CB} = 30 V) (V_{CB} = 30 V, T_A = 150 °C)	I_{CBO}	 – –	 – –	 15 5.0	 nA μA
ON CHARACTERISTICS					
DC Current Gain (I_C = 10 μA, V_{CE} = 5.0 V) BC846B, BC847B BC848C (I_C = 2.0 mA, V_{CE} = 5.0 V) BC846B, BC847B BC848C	h_{FE}	 – – 200 420	 150 270 290 520	 – – 475 800	–
Collector-Emitter Saturation Voltage (I_C = 10 mA, I_B = 0.5 mA) All devices except SBC847BPDW1T1G SBC847BPDW1T1G only (I_C = 100 mA, I_B = 5.0 mA) All devices (I_C = 2 mA, I_B = 0.5 mA) SBC847BPDW1T1G only	$V_{CE(sat)}$	 – – – –	 – – – 0.024	 0.25 0.1 0.6 –	V
Base-Emitter Saturation Voltage (I_C = 10 mA, I_B = 0.5 mA) (I_C = 100 mA, I_B = 5.0 mA)	$V_{BE(sat)}$	 – –	 0.7 0.9	 – –	V
Base-Emitter Voltage (I_C = 2.0 mA, V_{CE} = 5.0 V) (I_C = 10 mA, V_{CE} = 5.0 V)	$V_{BE(on)}$	 580 –	 660 –	 700 770	mV
SMALL-SIGNAL CHARACTERISTICS					
Current-Gain – Bandwidth Product (I_C = 10 mA, V_{CE} = 5.0 Vdc, f = 100 MHz)	f_T	 100	 –	 –	MHz
Output Capacitance (V_{CB} = 10 V, f = 1.0 MHz)	C_{obo}	–	–	4.5	pF
Noise Figure (I_C = 0.2 mA, V_{CE} = 5.0 Vdc, R_S = 2.0 kΩ, f = 1.0 kHz, BW = 200 Hz)	NF	 –	 –	 10	dB

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (PNP) (T_A = 25 °C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector - Emitter Breakdown Voltage (I_C = −10 mA)	$V_{(BR)CEO}$				V
BC846		−65	–	–	
BC847		−45	–	–	
BC848		−30	–	–	
Collector - Emitter Breakdown Voltage (I_C = −10 μA, V_{EB} = 0)	$V_{(BR)CES}$				V
BC846		−80	–	–	
BC847		−50	–	–	
BC848		−30	–	–	
Collector - Base Breakdown Voltage (I_C = −10 μA)	$V_{(BR)CBO}$				V
BC846		−80	–	–	
BC847		−50	–	–	
BC848		−30	–	–	
Emitter - Base Breakdown Voltage (I_E = −1.0 μA)	$V_{(BR)EBO}$				V
BC846		−6.0	–	–	
BC847		−6.0	–	–	
BC848		−6.0	–	–	
Collector Cutoff Current	I_{CBO}				
(V_{CB} = −30 V)		–	–	−15	nA
(V_{CB} = −30 V, T_A = 150 °C)		–	–	−4.0	μA
ON CHARACTERISTICS					
DC Current Gain	h_{FE}				–
(I_C = −10 μA, V_{CE} = −5.0 V)					
BC846B, BC847B		–	150	–	
BC848C		–	270	–	
(I_C = −2.0 mA, V_{CE} = −5.0 V)					
BC846B, BC847B		200	290	475	
BC848C		420	520	800	
Collector - Emitter Saturation Voltage	$V_{CE(sat)}$				V
(I_C = −10 mA, I_B = −0.5 mA) All devices except SBC847BPDW1T1G		–	–	−0.3	
SBC847BPDW1T1G only		–	–	−0.1	
(I_C = −100 mA, I_B = −5.0 mA) All devices		–	–	−0.65	
(I_C = −2 mA, I_B = −0.5 mA) SBC847BPDW1T1G only		–	−0.024	–	
Base - Emitter Saturation Voltage	$V_{BE(sat)}$				V
(I_C = −10 mA, I_B = −0.5 mA)		–	−0.7	–	
(I_C = −100 mA, I_B = −5.0 mA)		–	−0.9	–	
Base - Emitter On Voltage	$V_{BE(on)}$				V
(I_C = −2.0 mA, V_{CE} = −5.0 V)		−0.6	–	−0.75	
(I_C = −10 mA, V_{CE} = −5.0 V)		–	–	−0.82	
SMALL-SIGNAL CHARACTERISTICS					
Current - Gain – Bandwidth Product (I_C = −10 mA, V_{CE} = −5.0 Vdc, f = 100 MHz)	f_T	100	–	–	MHz
Output Capacitance (V_{CB} = −10 V, f = 1.0 MHz)	C_{ob}	–	–	4.5	pF
Noise Figure (I_C = −0.2 mA, V_{CE} = −5.0 Vdc, R_S = 2.0 kΩ, f = 1.0 kHz, BW = 200 Hz)	NF	–	–	10	dB

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

TYPICAL NPN CHARACTERISTICS – BC846




Figure 1. DC Current Gain vs. Collector Current




Figure 2. Collector Emitter Saturation Voltage vs. Collector Current




Figure 3. Base Emitter Saturation Voltage vs. Collector Current




Figure 4. Base Emitter Voltage vs. Collector Current




Figure 5. Collector Saturation Region




Figure 6. Base-Emitter Temperature Coefficient

Share Feedback
Your Opinion Matters

TYPICAL NPN CHARACTERISTICS – BC846




Figure 7. Capacitance




Figure 8. Current-Gain – Bandwidth Product

Share Feedback
Your Opinion Matters

TYPICAL PNP CHARACTERISTICS — BC846




Figure 9. DC Current Gain vs. Collector Current




Figure 10. Collector Emitter Saturation Voltage vs. Collector Current




Figure 11. Base Emitter Saturation Voltage vs. Collector Current




Figure 12. Base Emitter Voltage vs. Collector Current




Figure 13. Collector Saturation Region




Figure 14. Base-Emitter Temperature Coefficient

Share Feedback
Your Opinion Matters

TYPICAL PNP CHARACTERISTICS — BC846




Figure 15. Capacitance




Figure 16. Current-Gain – Bandwidth Product

Share Feedback
Your Opinion Matters

TYPICAL NPN CHARACTERISTICS – BC847




Figure 17. DC Current Gain vs. Collector Current




Figure 18. Collector Emitter Saturation Voltage vs. Collector Current




Figure 19. Base Emitter Saturation Voltage vs. Collector Current




Figure 20. Base Emitter Voltage vs. Collector Current




Figure 21. Collector Saturation Region




Figure 22. Base-Emitter Temperature Coefficient

Share Feedback
Your Opinion Matters

TYPICAL NPN CHARACTERISTICS – BC847




Figure 23. Capacitances




Figure 24. Current-Gain – Bandwidth Product

Share Feedback
Your Opinion Matters

TYPICAL PNP CHARACTERISTICS – BC847




Figure 25. DC Current Gain vs. Collector Current




Figure 26. Collector Emitter Saturation Voltage vs. Collector Current




Figure 27. Base Emitter Saturation Voltage vs. Collector Current




Figure 28. Base Emitter Voltage vs. Collector Current




Figure 29. Collector Saturation Region




Figure 30. Base-Emitter Temperature Coefficient

Share Feedback
Your Opinion Matters

TYPICAL PNP CHARACTERISTICS – BC847




Figure 31. Capacitances




Figure 32. Current-Gain – Bandwidth Product

Share Feedback
Your Opinion Matters

TYPICAL NPN CHARACTERISTICS – BC848




Figure 33. DC Current Gain vs. Collector Current




Figure 34. Collector Emitter Saturation Voltage vs. Collector Current




Figure 35. Base Emitter Saturation Voltage vs. Collector Current




Figure 36. Base Emitter Voltage vs. Collector Current




Figure 37. Collector Saturation Region




Figure 38. Base-Emitter Temperature Coefficient

Share Feedback
Your Opinion Matters

TYPICAL NPN CHARACTERISTICS – BC848




Figure 39. Capacitances




Figure 40. Current-Gain – Bandwidth Product

Share Feedback
Your Opinion Matters

TYPICAL PNP CHARACTERISTICS – BC848




Figure 41. DC Current Gain vs. Collector Current




Figure 42. Collector Emitter Saturation Voltage vs. Collector Current




Figure 43. Base Emitter Saturation Voltage vs. Collector Current




Figure 44. Base Emitter Voltage vs. Collector Current




Figure 45. Collector Saturation Region




Figure 46. Base-Emitter Temperature Coefficient

Share Feedback
Your Opinion Matters

TYPICAL PNP CHARACTERISTICS – BC848




Figure 47. Capacitances




Figure 48. Current-Gain – Bandwidth Product

Share Feedback
Your Opinion Matters




Figure 49. Thermal Response




Figure 50. Safe Operating Area – BC846

The safe operating area curves indicate I_C–V_{CE} limits of the transistor that must be observed for reliable operation. Collector load lines for specific circuits must fall below the limits indicated by the applicable curve.

The data of Figure 50 is based upon $T_{J(pk)}$ = 150 °C; T_C or T_A is variable depending upon conditions. Pulse curves are valid for duty cycles to 10% provided $T_{J(pk)} \le 150$ °C. $T_{J(pk)}$ may be calculated from the data in Figure 49. At high case or ambient temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by the secondary breakdown.




Figure 51. Safe Operating Area – BC847




Figure 52. Safe Operating Area – BC848

Share Feedback
Your Opinion Matters

ORDERING INFORMATION

Device	Marking	Package	Shipping†
BC846BPDW1T1G BC846BPDW1T1G-NC SBC846BPDW1T1G* SBC846BPDW1T1G-NC*	BB	SC-88 (Pb-Free)	3,000 / Tape & Reel
SBC846BPDW1T2G* SBC846BPDW1T2G-NC*			
SBC846BPDW1T3G* SBC846BPDW1T3G-NC*			10,000 / Tape & Reel
BC847BPDW1T1G BC847BPDW1T1G-NC SBC847BPDW1T1G* SBC847BPDW1T1G-NC*	BF	SC-88 (Pb-Free)	3,000 / Tape & Reel
BC847BPDW1T2G BC847BPDW1T2G-NC			
BC847BPDW1T3G BC847BPDW1T3G-NC SBC847BPDW1T3G* SBC847BPDW1T3G-NC*			10,000 / Tape & Reel
BC848CPDW1T1G BC848CPDW1T1G-NC	BL	SC-88 (Pb-Free)	3,000 / Tape & Reel

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

* S, V and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

Share Feedback
Your Opinion Matters

REVISION HISTORY

Revision	Description of Changes	Date
14	Added -NC device variants to the datasheet. Updated Ordering Information to include both standard and -NC OPNs. Moved this table to page 17.	10/22/2026


This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.

Share Feedback
Your Opinion Matters




SC−88 2.00x1.25x0.90, 0.65P
CASE 419B−02
ISSUE Z


DATE 18 APR 2024




TOP VIEW



SIDE VIEW



END VIEW




DETAIL A
SCALE 2:1

NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5−2018.
2. ALL DIMENSION ARE IN MILLIMETERS.
3. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.20 PER END.
4. DIMENSIONS D AND E1 AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AND DATUM H.
5. DATUMS A AND B ARE DETERMINED AT DATUM H.
6. DIMENSIONS b AND c APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08 AND 0.15 FROM THE TIP.
7. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 TOTAL IN EXCESS OF DIMENSION b AT MAXIMUM MATERIAL CONDITION. THE DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT.


	MILLIMETERS		
DIM	MIN.	NOM.	MAX.
A	−−−	−−−	1.10
A1	0.00	−−−	0.10
A2	0.70	0.90	1.00
b	0.15	0.20	0.25
c	0.08	0.15	0.22
D	2.00 BSC		
E	2.10 BSC		
E1	1.25 BSC		
e	0.65 BSC		
L	0.26	0.36	0.46
L2	0.15 BSC		
aaa	0.15		
bbb	0.30		
ccc	0.10		
ddd	0.10		



RECOMMENDED MOUNTING FOOTPRINT*

* FOR ADDITIONAL INFORMATION ON OUR Pb−FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ONSEMI SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXX = Specific Device Code
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation and/or position may vary depending upon manufacturing location.

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42985B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**SC−88 2.00x1.25x0.90, 0.65P**		**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

SC−88 2.00x1.25x0.90, 0.65P
CASE 419B−02
ISSUE Z

DATE 18 APR 2024

STYLE 1:
PIN 1. EMITTER 2
2. BASE 2
3. COLLECTOR 1
4. EMITTER 1
5. BASE 1
6. COLLECTOR 2

STYLE 2:
CANCELLED

STYLE 3:
CANCELLED

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. COLLECTOR
4. EMITTER
5. BASE
6. ANODE

STYLE 5:
PIN 1. ANODE
2. ANODE
3. COLLECTOR
4. EMITTER
5. BASE
6. CATHODE

STYLE 6:
PIN 1. ANODE 2
2. N/C
3. CATHODE 1
4. ANODE 1
5. N/C
6. CATHODE 2

STYLE 7:
PIN 1. SOURCE 2
2. DRAIN 2
3. GATE 1
4. SOURCE 1
5. DRAIN 1
6. GATE 2

STYLE 8:
CANCELLED

STYLE 9:
PIN 1. EMITTER 2
2. EMITTER 1
3. COLLECTOR 1
4. BASE 1
5. BASE 2
6. COLLECTOR 2

STYLE 10:
PIN 1. SOURCE 2
2. SOURCE 1
3. GATE 1
4. DRAIN 1
5. DRAIN 2
6. GATE 2

STYLE 11:
PIN 1. CATHODE 2
2. CATHODE 2
3. ANODE 1
4. CATHODE 1
5. CATHODE 1
6. ANODE 2

STYLE 12:
PIN 1. ANODE 2
2. ANODE 2
3. CATHODE 1
4. ANODE 1
5. ANODE 1
6. CATHODE 2

STYLE 13:
PIN 1. ANODE
2. N/C
3. COLLECTOR
4. EMITTER
5. BASE
6. CATHODE

STYLE 14:
PIN 1. VREF
2. GND
3. GND
4. IOUT
5. VEN
6. VCC

STYLE 15:
PIN 1. ANODE 1
2. ANODE 2
3. ANODE 3
4. CATHODE 3
5. CATHODE 2
6. CATHODE 1

STYLE 16:
PIN 1. BASE 1
2. EMITTER 2
3. COLLECTOR 2
4. BASE 2
5. EMITTER 1
6. COLLECTOR 1

STYLE 17:
PIN 1. BASE 1
2. EMITTER 1
3. COLLECTOR 2
4. BASE 2
5. EMITTER 2
6. COLLECTOR 1

STYLE 18:
PIN 1. VIN1
2. VCC
3. VOUT2
4. VIN2
5. GND
6. VOUT1

STYLE 19:
PIN 1. I OUT
2. GND
3. GND
4. V CC
5. V EN
6. V REF

STYLE 20:
PIN 1. COLLECTOR
2. COLLECTOR
3. BASE
4. EMITTER
5. COLLECTOR
6. COLLECTOR

STYLE 21:
PIN 1. ANODE 1
2. N/C
3. ANODE 2
4. CATHODE 2
5. N/C
6. CATHODE 1

STYLE 22:
PIN 1. D1 (i)
2. GND
3. D2 (i)
4. D2 (c)
5. VBUS
6. D1 (c)

STYLE 23:
PIN 1. Vn
2. CH1
3. Vp
4. N/C
5. CH2
6. N/C

STYLE 24:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. CATHODE
5. CATHODE
6. CATHODE

STYLE 25:
PIN 1. BASE 1
2. CATHODE
3. COLLECTOR 2
4. BASE 2
5. EMITTER
6. COLLECTOR 1

STYLE 26:
PIN 1. SOURCE 1
2. GATE 1
3. DRAIN 2
4. SOURCE 2
5. GATE 2
6. DRAIN 1

STYLE 27:
PIN 1. BASE 2
2. BASE 1
3. COLLECTOR 1
4. EMITTER 1
5. EMITTER 2
6. COLLECTOR 2

STYLE 28:
PIN 1. DRAIN
2. DRAIN
3. GATE
4. SOURCE
5. DRAIN
6. DRAIN

STYLE 29:
PIN 1. ANODE
2. ANODE
3. COLLECTOR
4. EMITTER
5. BASE/ANODE
6. CATHODE

STYLE 30:
PIN 1. SOURCE 1
2. DRAIN 2
3. DRAIN 2
4. SOURCE 2
5. GATE 1
6. DRAIN 1

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

DOCUMENT NUMBER:	**98ASB42985B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SC−88 2.00x1.25x0.90, 0.65P**		**PAGE 2 OF 2**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales