
Switching Transistor


PNP Silicon

MMBT4403L, SMMBT4403L



Features

- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant



SOT−23 (TO−236)
CASE 318
STYLE 6

MAXIMUM RATINGS


Rating	Symbol	Value	Unit
Collector − Emitter Voltage	V_{CEO}	−40	Vdc
Collector − Base Voltage	V_{CBO}	−40	Vdc
Emitter − Base Voltage	V_{EBO}	−5.0	Vdc
Collector Current − Continuous	I_C	−600	mAdc
Collector Current − Peak	I_{CM}	−900	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR− 5 Board (Note 1) @T_A = 25°C Derate above 25°C	P_D	225 1.8	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	556	°C/W
Total Device Dissipation Alumina Substrate, (Note 2) @T_A = 25°C Derate above 25°C	P_D	300 2.4	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	417	°C/W
Junction and Storage Temperature	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
*Transient pulses must not cause the junction temperature to be exceeded.
1. FR−5 = 1.0 × 0.75 × 0.062 in.
2. Alumina = 0.4 × 0.3 × 0.024 in. 99.5% alumina.

MARKING DIAGRAM



2T = Specific Device Code*
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Specific Device Code, Date Code or overbar orientation and/or location may vary depending upon manufacturing location. This is a representation only and actual devices may not match this drawing exactly.

ORDERING INFORMATION

Device	Package	Shipping†
MMBT4403LT1G	SOT−23 (Pb−Free)	3000 / Tape & Reel
SMMBT4403LT1G	SOT−23 (Pb−Free)	3000 / Tape & Reel
MMBT4403LT3G	SOT−23 (Pb−Free)	10,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 1994

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector – Emitter Breakdown Voltage (Note 3)	(I_C = –1.0 mAdc, I_B = 0)	$V_{(BR)CEO}$	–40	–	Vdc
Collector – Base Breakdown Voltage	(I_C = –0.1 mAdc, I_E = 0)	$V_{(BR)CBO}$	–40	–	Vdc
Emitter – Base Breakdown Voltage	(I_E = –0.1 mAdc, I_C = 0)	$V_{(BR)EBO}$	–5.0	–	Vdc
Base Cutoff Current	(V_{CE} = –35 Vdc, V_{EB} = –0.4 Vdc)	I_{BEV}	–	–0.1	μAdc
Collector Cutoff Current	(V_{CE} = –35 Vdc, V_{EB} = –0.4 Vdc)	I_{CEX}	–	–0.1	μAdc
ON CHARACTERISTICS					
DC Current Gain		h_{FE}			–
	(I_C = –0.1 mAdc, V_{CE} = –1.0 Vdc)		30	–	
	(I_C = –1.0 mAdc, V_{CE} = –1.0 Vdc)		60	–	
	(I_C = –10 mAdc, V_{CE} = –1.0 Vdc)		100	–	
(Note 3)	(I_C = –150 mAdc, V_{CE} = –2.0 Vdc)		100	300	
(Note 3)	(I_C = –500 mAdc, V_{CE} = –2.0 Vdc)		20	–	
Collector – Emitter Saturation Voltage (Note 3)		$V_{CE(sat)}$			Vdc
	(I_C = –150 mAdc, I_B = –15 mAdc)		–	–0.4	
	(I_C = –500 mAdc, I_B = –50 mAdc)		–	–0.75	
Base – Emitter Saturation Voltage (Note 3)		$V_{BE(sat)}$			Vdc
	(I_C = –150 mAdc, I_B = –15 mAdc)		–0.75	–0.95	
	(I_C = –500 mAdc, I_B = –50 mAdc)		–	–1.3	
SMALL– SIGNAL CHARACTERISTICS					
Current – Gain – Bandwidth Product	(I_C = –20 mAdc, V_{CE} = –10 Vdc, f = 100 MHz)	f_T	200	–	MHz
Collector–Base Capacitance	(V_{CB} = –10 Vdc, I_E = 0, f = 1.0 MHz)	C_{cb}	–	8.5	pF
Emitter–Base Capacitance	(V_{BE} = –0.5 Vdc, I_C = 0, f = 1.0 MHz)	C_{eb}	–	30	pF
Input Impedance	(I_C = –1.0 mAdc, V_{CE} = –10 Vdc, f = 1.0 kHz)	h_{ie}	1.5	15	kΩ
Voltage Feedback Ratio	(I_C = –1.0 mAdc, V_{CE} = –10 Vdc, f = 1.0 kHz)	h_{re}	0.1	8.0	X 10^{-4}
Small – Signal Current Gain	(I_C = –1.0 mAdc, V_{CE} = –10 Vdc, f = 1.0 kHz)	h_{fe}	60	500	–
Output Admittance	(I_C = –1.0 mAdc, V_{CE} = –10 Vdc, f = 1.0 kHz)	h_{oe}	1.0	100	μMhos
SWITCHING CHARACTERISTICS					
Delay Time	(V_{CC} = –30 Vdc, V_{EB} = –2.0 Vdc, I_C = –150 mAdc, I_{B1} = –15 mAdc)	t_d	–	15	ns
Rise Time		t_r	–	20	
Storage Time	(V_{CC} = –30 Vdc, I_C = –150 mAdc, I_{B1} = I_{B2} = –15 mAdc)	t_s	–	225	ns
Fall Time		t_f	–	30	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

SWITCHING TIME EQUIVALENT TEST CIRCUIT




Figure 1. Turn–On Time




Figure 2. Turn–Off Time

Scope rise time < 4.0 ns

*Total shunt capacitance of test jig connectors, and oscilloscope

Share Feedback
Your Opinion Matters

TRANSIENT CHARACTERISTICS




Figure 3. Charge Data

Figure 4. Turn−On Time




Figure 5. Rise Time

Figure 6. Storage Time

SMALL−SIGNAL CHARACTERISTICS NOISE FIGURE

V_{CE} = −10 Vdc, T_A = 25°C; Bandwidth = 1.0 Hz




Figure 7. Frequency Effects

Figure 8. Source Resistance Effects

Share Feedback
Your Opinion Matters

h PARAMETERS

V_{CE} = 10 Vdc, f = 1.0 kHz, T_A = 25°C

This group of graphs illustrates the relationship between h_{fe} and other “h” parameters for this series of transistors. To obtain these curves, a high−gain and a low−gain unit were selected from the MMBT4403LT1 lines, and the same units were used to develop the correspondingly numbered curves on each graph.




Figure 9. Input Impedance




Figure 10. Voltage Feedback Ratio




Figure 11. Output Admittance

Share Feedback
Your Opinion Matters

STATIC CHARACTERISTICS




Figure 12. DC Current Gain




Figure 13. Collector Saturation Region




Figure 14. Collector−Emitter Saturation Voltage vs. Collector Current




Figure 15. Temperature Coefficients

Share Feedback
Your Opinion Matters

STATIC CHARACTERISTICS




Figure 16. Base−Emitter Saturation Voltage vs. Collector Current




Figure 17. Base−Emitter Turn On Voltage vs. Collector Current




Figure 18. Input Capacitance vs. Emitter Base Voltage




Figure 19. Output Capacitance vs. Collector Base Voltage




Figure 20. Safe Operating Area





Figure 21. Current−Gain−Bandwidth Product


Share Feedback
Your Opinion Matters




SCALE 4:1

SOT−23 (TO−236) 2.90x1.30x1.00 1.90P
CASE 318
ISSUE AU


DATE 14 AUG 2024




TOP VIEW



DETAIL "A"
Scale 3:1



SIDE VIEW




END VIEW

MILLIMETERS			
DIM	MIN	NOM	MAX
A	0.89	1.00	1.11
A1	0.01	0.06	0.10
b	0.37	0.44	0.50
c	0.08	0.14	0.20
D	2.80	2.90	3.04
E	1.20	1.30	1.40
e	1.78	1.90	2.04
L	0.30	0.43	0.55
L1	0.35	0.54	0.69
H_E	2.10	2.40	2.64
T	0°	−−−	10°


NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSIONS: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

GENERIC
MARKING DIAGRAM*



XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.



RECOMMENDED
MOUNTING FOOTPRINT

* For additional information on our Pb−Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42226B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOT−23 (TO−236) 2.90x1.30x1.00 1.90P**		**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

SOT−23 (TO−236) 2.90x1.30x1.00 1.90P
CASE 318
ISSUE AU

DATE 14 AUG 2024

STYLE 1 THRU 5:
CANCELLED

STYLE 6:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 7:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

STYLE 8:
PIN 1. ANODE
2. NO CONNECTION
3. CATHODE

STYLE 9:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 10:
PIN 1. DRAIN
2. SOURCE
3. GATE

STYLE 11:
PIN 1. ANODE
2. CATHODE
3. CATHODE−ANODE

STYLE 12:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 13:
PIN 1. SOURCE
2. DRAIN
3. GATE

STYLE 14:
PIN 1. CATHODE
2. GATE
3. ANODE

STYLE 15:
PIN 1. GATE
2. CATHODE
3. ANODE

STYLE 16:
PIN 1. ANODE
2. CATHODE
3. CATHODE

STYLE 17:
PIN 1. NO CONNECTION
2. ANODE
3. CATHODE

STYLE 18:
PIN 1. NO CONNECTION
2. CATHODE
3. ANODE

STYLE 19:
PIN 1. CATHODE
2. ANODE
3. CATHODE−ANODE

STYLE 20:
PIN 1. CATHODE
2. ANODE
3. GATE

STYLE 21:
PIN 1. GATE
2. SOURCE
3. DRAIN

STYLE 22:
PIN 1. RETURN
2. OUTPUT
3. INPUT

STYLE 23:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 24:
PIN 1. GATE
2. DRAIN
3. SOURCE

STYLE 25:
PIN 1. ANODE
2. CATHODE
3. GATE

STYLE 26:
PIN 1. CATHODE
2. ANODE
3. NO CONNECTION

STYLE 27:
PIN 1. CATHODE
2. CATHODE
3. CATHODE

STYLE 28:
PIN 1. ANODE
2. ANODE
3. ANODE

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales