# Digital Transistors (BRT)
# R1 = 10 kΩ, R2 = 10 kΩ

## PNP Transistors with Monolithic Bias Resistor Network

# MUN2111, MMUN2111L, MUN5111, DTA114EE, DTA114EM3, NSBA114EF3

This series of digital transistors is designed to replace a single device and its external resistor bias network. The Bias Resistor Transistor (BRT) contains a single transistor with a monolithic bias network consisting of two resistors; a series base resistor and a base-emitter resistor. The BRT eliminates these individual components by integrating them into a single device. The use of a BRT can reduce both system cost and board space.

### Features


- Simplifies Circuit Design
- Reduces Board Space
- Reduces Component Count
- S and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### MAXIMUM RATINGS ($T_A$ = 25 °C)


| Rating | Symbol | Max | Unit |
|---|---|---|---|
| Collector-Base Voltage | $V_{CBO}$ | 50 | Vdc |
| Collector-Emitter Voltage | $V_{CEO}$ | 50 | Vdc |
| Collector Current – Continuous | $I_C$ | 100 | mAdc |
| Input Forward Voltage | $V_{IN(fwd)}$ | 40 | Vdc |
| Input Reverse Voltage | $V_{IN(rev)}$ | 10 | Vdc |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


### PIN CONNECTIONS





### MARKING DIAGRAMS




**SC-59**
**CASE 318D**
**STYLE 1**




**SOT-23**
**CASE 318**
**STYLE 6**




**SC-70/SOT-323**
**CASE 419**
**STYLE 3**




**SC-75**
**CASE 463**
**STYLE 1**




**SOT-723**
**CASE 631AA**
**STYLE 1**




**SOT-1123**
**CASE 524AA**
**STYLE 1**

XXX = Specific Device Code
M = Date Code*
▪ = Pb-Free Package

(Note: Microdot may be in either location)

* Date Code orientation may vary depending upon manufacturing location.

### ORDERING INFORMATION

See detailed ordering, marking, and shipping information in the package dimensions section on page 2 of this data sheet.


© Semiconductor Components Industries, LLC, 2000

**Table 1. ORDERING INFORMATION**

| Device | Part Marking | Package | Shipping† |
|---|---|---|---|
| MUN2111T1G<br>SMUN2111T1G* | 6A | SC-59<br>(Pb-Free) | 3000 / Tape & Reel |
| SMUN2111T3G* | | | 10000 / Tape & Reel |
| MMUN2111LT1G<br>MMUN2111LT1G-NC<br>SMMUN2111LT1G*<br>SMMUN2111LT1G-NC* | A6A | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel |
| MMUN2111LT3G<br>MMUN2111LT3G-NC<br>SMMUN2111LT3G*<br>SMMUN2111LT3G-NC* | | | 10000 / Tape & Reel |
| MUN5111T1G<br>MUN5111T1G-NC<br>SMUN5111T1G*<br>SMUN5111T1G-NC* | 6A | SC-70/SOT-323<br>(Pb-Free) | 3000 / Tape & Reel |
| DTA114EET1G<br>DTA114EET1G-NC (Under Development)<br>NSVDTA114EET1G*<br>NSVDTA114EET1G-NC* (Under Development) | 6A | SC-75<br>(Pb-Free) | 3000 / Tape & Reel |
| DTA114EM3T5G<br>DTA114EM3T5G-NC (Under Development)<br>NSVDTA114EM3T5G*<br>NSVDTA114EM3T5G-NC* (Under Development) | 6A | SOT-723<br>(Pb-Free) | 8000 / Tape & Reel |

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

* S, V and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable




(1) SC-75 and SC-70/SOT-323; Minimum Pad
(2) SC-59; Minimum Pad
(3) SOT-23; Minimum Pad
(4) SOT-1123; 100 $mm^2$, 1 oz. copper trace
(5) SOT-723; Minimum Pad

**Figure 1. Derating Curve**



Share Feedback
Your Opinion Matters

**Table 2. THERMAL CHARACTERISTICS**

| Characteristic | Symbol | Max | Unit |
|---|---|---|---|
| **THERMAL CHARACTERISTICS (SC-59) (MUN2111)** | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C (Note 1)<br>(Note 2)<br>Derate above 25 °C (Note 1)<br>(Note 2) | $P_D$ | <br>230<br>338<br>1.8<br>2.7 | <br>mW<br><br>mW/°C |
| Thermal Resistance, Junction to Ambient (Note 1)<br>(Note 2) | $R_{\theta JA}$ | 540<br>370 | °C/W |
| Thermal Resistance, Junction to Lead (Note 1)<br>(Note 2) | $R_{\theta JL}$ | 264<br>287 | °C/W |
| Junction and Storage Temperature Range | $T_J$, $T_{stg}$ | −55 to +150 | °C |
| **THERMAL CHARACTERISTICS (SOT-23) (MMUN2111L)** | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C (Note 1)<br>(Note 2)<br>Derate above 25 °C (Note 1)<br>(Note 2) | $P_D$ | <br>246<br>400<br>2.0<br>3.2 | <br>mW<br><br>mW/°C |
| Thermal Resistance, Junction to Ambient (Note 1)<br>(Note 2) | $R_{\theta JA}$ | 508<br>311 | °C/W |
| Thermal Resistance, Junction to Lead (Note 1)<br>(Note 2) | $R_{\theta JL}$ | 174<br>208 | °C/W |
| Junction and Storage Temperature Range | $T_J$, $T_{stg}$ | −55 to +150 | °C |
| **THERMAL CHARACTERISTICS (SC-70/SOT-323) (MUN5111)** | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C (Note 1)<br>(Note 2)<br>Derate above 25 °C (Note 1)<br>(Note 2) | $P_D$ | <br>202<br>310<br>1.6<br>2.5 | <br>mW<br><br>mW/°C |
| Thermal Resistance, Junction to Ambient (Note 1)<br>(Note 2) | $R_{\theta JA}$ | 618<br>403 | °C/W |
| Thermal Resistance, Junction to Lead (Note 1)<br>(Note 2) | $R_{\theta JL}$ | 280<br>332 | °C/W |
| Junction and Storage Temperature Range | $T_J$, $T_{stg}$ | −55 to +150 | °C |
| **THERMAL CHARACTERISTICS (SC-75) (DTA114EE)** | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C (Note 1)<br>(Note 2)<br>Derate above 25 °C (Note 1)<br>(Note 2) | $P_D$ | <br>200<br>300<br>1.6<br>2.4 | <br>mW<br><br>mW/°C |
| Thermal Resistance, Junction to Ambient (Note 1)<br>(Note 2) | $R_{\theta JA}$ | 600<br>400 | °C/W |
| Junction and Storage Temperature Range | $T_J$, $T_{stg}$ | −55 to +150 | °C |
| **THERMAL CHARACTERISTICS (SOT-723) (DTA114EM3)** | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C (Note 1)<br>(Note 2)<br>Derate above 25 °C (Note 1)<br>(Note 2) | $P_D$ | <br>260<br>600<br>2.0<br>4.8 | <br>mW<br><br>mW/°C |
| Thermal Resistance, Junction to Ambient (Note 1)<br>(Note 2) | $R_{\theta JA}$ | 480<br>205 | °C/W |
| Junction and Storage Temperature Range | $T_J$, $T_{stg}$ | −55 to +150 | °C |

1. FR-4 @ Minimum Pad.
2. FR-4 @ 1.0 x 1.0 Inch Pad.
3. FR-4 @ 100 $mm^2$, 1 oz. copper traces, still air.
4. FR-4 @ 500 $mm^2$, 1 oz. copper traces, still air.



Share Feedback
Your Opinion Matters

**Table 2. THERMAL CHARACTERISTICS** (continued)

| Characteristic | Symbol | Max | Unit |
|---|---|---|---|
| **THERMAL CHARACTERISTICS (SOT-1123) (NSBA114EF3)** | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C (Note 3)<br>(Note 4)<br>Derate above 25 °C (Note 3)<br>(Note 4) | $P_D$ | <br>254<br>297<br>2.0<br>2.4 | <br>mW<br><br>mW/°C |
| Thermal Resistance, Junction to Ambient (Note 3)<br>(Note 4) | $R_{\theta JA}$ | 493<br>421 | °C/W |
| Thermal Resistance, Junction to Lead (Note 3) | $R_{\theta JL}$ | 193 | °C/W |
| Junction and Storage Temperature Range | $T_J$, $T_{stg}$ | −55 to +150 | °C |

1. FR-4 @ Minimum Pad.
2. FR-4 @ 1.0 x 1.0 Inch Pad.
3. FR-4 @ 100 $mm^2$, 1 oz. copper traces, still air.
4. FR-4 @ 500 $mm^2$, 1 oz. copper traces, still air.

**Table 3. ELECTRICAL CHARACTERISTICS** ($T_A$ = 25°C, unless otherwise noted)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|---|---|---|---|---|---|
| **OFF CHARACTERISTICS** | | | | | |
| Collector-Base Cutoff Current ($V_{CB}$ = 50 V, $I_E$ = 0) | $I_{CBO}$ | | | 100 | nAdc |
| Collector-Emitter Cutoff Current ($V_{CE}$ = 50 V, $I_B$ = 0) | $I_{CEO}$ | | | 500 | nAdc |
| Emitter-Base Cutoff Current ($V_{EB}$ = 6.0 V, $I_C$ = 0) | $I_{EBO}$ | | | 0.5 | mAdc |
| Collector-Base Breakdown Voltage ($I_C$ = 10 μA, $I_E$ = 0) | $V_{(BR)CBO}$ | 50 | | | Vdc |
| Collector-Emitter Breakdown Voltage (Note 5) ($I_C$ = 2.0 mA, $I_B$ = 0) | $V_{(BR)CEO}$ | 50 | | | Vdc |
| **ON CHARACTERISTICS** | | | | | |
| DC Current Gain (Note 5) ($I_C$ = 5.0 mA, $V_{CE}$ = 10 V) | $h_{FE}$ | 35 | 60 | | |
| Collector-Emitter Saturation Voltage (Note 5) ($I_C$ = 10 mA, $I_B$ = 0.3 mA) | $V_{CE(sat)}$ | | | 0.25 | Vdc |
| Input Voltage (off) ($V_{CE}$ = 5.0 V, $I_C$ = 100 μA) | $V_{i(off)}$ | | 1.2 | 0.8 | Vdc |
| Input Voltage (on) ($V_{CE}$ = 0.3 V, $I_C$ = 10 mA) | $V_{i(on)}$ | 2.5 | 1.8 | | Vdc |
| Output Voltage (on) ($V_{CC}$ = 5.0 V, $V_B$ = 2.5 V, $R_L$ = 1.0 kΩ) | $V_{OL}$ | | | 0.2 | Vdc |
| Output Voltage (off) ($V_{CC}$ = 5.0 V, $V_B$ = 0.5 V, $R_L$ = 1.0 kΩ) | $V_{OH}$ | 4.9 | | | Vdc |
| Input Resistor | R1 | 7.0 | 10 | 13 | kΩ |
| Resistor Ratio | $R_1/R_2$ | 0.8 | 1.0 | 1.2 | |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. Pulsed Condition: Pulse Width = 300 ms, Duty Cycle ≤ 2%.



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS
## MUN2111, MMUN2111L, MUN5111, DTA114EE, DTA114EM3





**Figure 2. $V_{CE(sat)}$ vs. $I_C$**





**Figure 3. DC Current Gain**





**Figure 4. Output Capacitance**





**Figure 5. Output Current vs. Input Voltage**





**Figure 6. Input Voltage vs. Output Current**



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS – NSBA114EF3





**Figure 7. $V_{CE(sat)}$ vs. $I_C$**





**Figure 8. DC Current Gain**





**Figure 9. Output Capacitance**





**Figure 10. Output Current vs. Input Voltage**





**Figure 11. Input Voltage vs. Output Current**



Share Feedback
Your Opinion Matters


## REVISION HISTORY

| Revision | Description of Changes | Date |
|---|---|---|
| 11 | Ordering Information table update. | 10/23/2026 |

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.




Share Feedback
Your Opinion Matters




**SCALE 4:1**

**SOT−23 (TO−236) 2.90x1.30x1.00 1.90P**
CASE 318
ISSUE AU


DATE 14 AUG 2024





TOP VIEW




DETAIL "A"
Scale 3:1




SIDE VIEW





END VIEW

| MILLIMETERS | | | |
|---|---|---|---|
| DIM | MIN | NOM | MAX |
| A | 0.89 | 1.00 | 1.11 |
| A1 | 0.01 | 0.06 | 0.10 |
| b | 0.37 | 0.44 | 0.50 |
| c | 0.08 | 0.14 | 0.20 |
| D | 2.80 | 2.90 | 3.04 |
| E | 1.20 | 1.30 | 1.40 |
| e | 1.78 | 1.90 | 2.04 |
| L | 0.30 | 0.43 | 0.55 |
| L1 | 0.35 | 0.54 | 0.69 |
| $H_E$ | 2.10 | 2.40 | 2.64 |
| T | 0° | −−− | 10° |


NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSIONS: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

**GENERIC**
**MARKING DIAGRAM***




XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.




RECOMMENDED
MOUNTING FOOTPRINT

* For additional information on our Pb−Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**STYLES ON PAGE 2**

| | | | |
|---|---|---|---|
| **DOCUMENT NUMBER:** | **98ASB42226B** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. | |
| **DESCRIPTION:** | **SOT−23 (TO−236) 2.90x1.30x1.00 1.90P** | | **PAGE 1 OF 2** |

**onsemi** and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

**SOT−23 (TO−236) 2.90x1.30x1.00 1.90P**
CASE 318
ISSUE AU

DATE 14 AUG 2024

STYLE 1 THRU 5:
CANCELLED

STYLE 6:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 7:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

STYLE 8:
PIN 1. ANODE
2. NO CONNECTION
3. CATHODE

STYLE 9:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 10:
PIN 1. DRAIN
2. SOURCE
3. GATE

STYLE 11:
PIN 1. ANODE
2. CATHODE
3. CATHODE−ANODE

STYLE 12:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 13:
PIN 1. SOURCE
2. DRAIN
3. GATE

STYLE 14:
PIN 1. CATHODE
2. GATE
3. ANODE

STYLE 15:
PIN 1. GATE
2. CATHODE
3. ANODE

STYLE 16:
PIN 1. ANODE
2. CATHODE
3. CATHODE

STYLE 17:
PIN 1. NO CONNECTION
2. ANODE
3. CATHODE

STYLE 18:
PIN 1. NO CONNECTION
2. CATHODE
3. ANODE

STYLE 19:
PIN 1. CATHODE
2. ANODE
3. CATHODE−ANODE

STYLE 20:
PIN 1. CATHODE
2. ANODE
3. GATE

STYLE 21:
PIN 1. GATE
2. SOURCE
3. DRAIN

STYLE 22:
PIN 1. RETURN
2. OUTPUT
3. INPUT

STYLE 23:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 24:
PIN 1. GATE
2. DRAIN
3. SOURCE

STYLE 25:
PIN 1. ANODE
2. CATHODE
3. GATE

STYLE 26:
PIN 1. CATHODE
2. ANODE
3. NO CONNECTION


STYLE 27:
PIN 1. CATHODE
2. CATHODE
3. CATHODE

STYLE 28:
PIN 1. ANODE
2. ANODE
3. ANODE





**onsemi** and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019




**SC−59−3 2.90x1.50x1.15, 1.90P**
CASE 318D
ISSUE J


DATE 15 FEB 2024




TOP VIEW




SIDE VIEW





END VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5−2018.
2. ALL DIMENSION ARE IN MILLIMETERS.


| DIM | MILLIMETERS | | |
|---|---|---|---|
| | MIN. | NOM. | MAX. |
| A | 1.00 | 1.15 | 1.30 |
| A1 | 0.01 | 0.06 | 0.10 |
| b | 0.35 | 0.43 | 0.50 |
| c | 0.09 | 0.14 | 0.18 |
| D | 2.70 | 2.90 | 3.10 |
| E | 2.50 | 2.80 | 3.00 |
| E1 | 1.30 | 1.50 | 1.70 |
| e | 1.90 BSC | | |
| L | 0.20 | 0.40 | 0.60 |




RECOMMENDED MOUNTING FOOTPRINT*

* FOR ADDITIONAL INFORMATION ON OUR Pb−FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

**GENERIC MARKING DIAGRAM***




XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package*

(*Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. N.C.
3. CATHODE

STYLE 3:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 4:
PIN 1. CATHODE
2. N.C.
3. ANODE


STYLE 5:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 6:
PIN 1. ANODE
2. CATHODE
3. ANODE/CATHODE

| | | |
|---|---|---|
| **DOCUMENT NUMBER:** | **98ASB42664B** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. |
| **DESCRIPTION:** | **SC−59−3 2.90x1.50x1.15, 1.90P** | **PAGE 1 OF 1** |

**onsemi** and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.


© Semiconductor Components Industries, LLC, 2000



**SCALE 4:1**

**SC−70 (SOT−323)**
CASE 419
ISSUE R


DATE 11 OCT 2022




NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH


| | MILLIMETERS | | | INCHES | | |
|---|---|---|---|---|---|---|
| DIM | MIN. | NOM. | MAX. | MIN. | NOM. | MAX. |
| A | 0.80 | 0.90 | 1.00 | 0.032 | 0.035 | 0.040 |
| A1 | 0.00 | 0.05 | 0.10 | 0.000 | 0.002 | 0.004 |
| A2 | 0.70 REF | | | 0.028 BSC | | |
| b | 0.30 | 0.35 | 0.40 | 0.012 | 0.014 | 0.016 |
| c | 0.10 | 0.18 | 0.25 | 0.004 | 0.007 | 0.010 |
| D | 1.80 | 2.00 | 2.20 | 0.071 | 0.080 | 0.087 |
| E | 1.15 | 1.24 | 1.35 | 0.045 | 0.049 | 0.053 |
| e | 1.20 | 1.30 | 1.40 | 0.047 | 0.051 | 0.055 |
| e1 | 0.65 BSC | | | 0.026 BSC | | |
| L | 0.20 | 0.38 | 0.56 | 0.008 | 0.015 | 0.022 |
| $H_E$ | 2.00 | 2.10 | 2.40 | 0.079 | 0.083 | 0.095 |

## GENERIC MARKING DIAGRAM




XX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.




* For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

SOLDERING FOOTPRINT

STYLE 1:
CANCELLED

STYLE 2:
PIN 1. ANODE
2. N.C.
3. CATHODE

STYLE 3:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 6:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

STYLE 7:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 8:
PIN 1. GATE
2. SOURCE
3. DRAIN

STYLE 9:
PIN 1. ANODE
2. CATHODE
3. CATHODE−ANODE

STYLE 10:
PIN 1. CATHODE
2. ANODE
3. ANODE−CATHODE

STYLE 11:
PIN 1. CATHODE
2. CATHODE
3. CATHODE


| | | |
|---|---|---|
| **DOCUMENT NUMBER:** | **98ASB42819B** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. |
| **DESCRIPTION:** | **SC−70 (SOT−323)** | **PAGE 1 OF 1** |

**onsemi** and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.


**SC75−3 1.60x0.80x0.80, 1.00P**
CASE 463
ISSUE H

DATE 01 FEB 2024







TOP VIEW




SIDE VIEW





END VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5−2018.
2. ALL DIMENSION ARE IN MILLIMETERS.

| DIM | MILLIMETERS | | |
|---|---|---|---|
| | MIN. | NOM. | MAX. |
| A | 0.70 | 0.80 | 0.90 |
| A1 | 0.00 | 0.05 | 0.10 |
| A2 | | 0.80 REF. | |
| b | 0.15 | 0.20 | 0.30 |
| c | 0.10 | 0.15 | 0.25 |
| D | 1.55 | 1.60 | 1.65 |
| E | 1.50 | 1.60 | 1.70 |
| E1 | 0.70 | 0.80 | 0.90 |
| e | | 1.00 BSC | |
| L | 0.10 | 0.15 | 0.20 |

**GENERIC**
**MARKING DIAGRAM***




XX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.


STYLE 1:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. N/C
3. CATHODE

STYLE 3:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. GATE
2. SOURCE
3. DRAIN





RECOMMENDED MOUNTING FOOTPRINT*

* FOR ADDITIONAL INFORMATION ON OUR Pb−FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.


| | | | |
|---|---|---|---|
| **DOCUMENT NUMBER:** | **98ASB15184C** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. | |
| **DESCRIPTION:** | **SC75−3 1.60x0.80x0.80, 1.00P** | | **PAGE 1 OF 1** |

**onsemi** and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.




**SOT−1123 0.80x0.60x0.37, 0.35P**
CASE 524AA
ISSUE D


DATE 18 JAN 2024




TOP VIEW




SIDE VIEW




BOTTOM VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.


| MILLIMETERS | | | |
|---|---|---|---|
| DIM | MIN | NOM | MAX |
| A | 0.34 | 0.37 | 0.40 |
| b | 0.15 | 0.22 | 0.28 |
| b1 | 0.10 | 0.15 | 0.20 |
| c | 0.07 | 0.12 | 0.17 |
| D | 0.75 | 0.80 | 0.85 |
| E | 0.55 | 0.60 | 0.65 |
| e | 0.35 | 0.38 | 0.40 |
| H | 0.950 | 1.000 | 1.050 |
| L | 0.185 REF | | |
| L2 | 0.05 | 0.10 | 0.15 |

**GENERIC MARKING DIAGRAM***




X = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.




RECOMMENDED MOUNTING FOOTPRINT

*For additional information on our Pb−Free strategy and soldering details, please download th e ON Semiconductor Soldering and Mounting Techniques Reference manual, SOLDERRM/D.

STYLE 1:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. N/C
3. CATHODE

STYLE 3:
PIN 1. ANODE
2. ANODE
3. CATHODE


STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. GATE
2. SOURCE
3. DRAIN

| | | | |
|---|---|---|---|
| **DOCUMENT NUMBER:** | **98AON23134D** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. | |
| **DESCRIPTION:** | **SOT−1123 0.80x0.60x0.37, 0.35P** | | **PAGE 1 OF 1** |

**onsemi** and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2006




**SOT−723 1.20x0.80x0.50, 0.40P**
CASE 631AA
ISSUE E


DATE 24 JAN 2024

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.


| DIM | MILLIMETERS | | |
|---|---|---|---|
| | MIN. | NOM. | MAX. |
| A | 0.45 | 0.50 | 0.55 |
| b | 0.15 | 0.21 | 0.27 |
| b1 | 0.25 | 0.31 | 0.37 |
| c | 0.07 | 0.12 | 0.17 |
| D | 1.15 | 1.20 | 1.25 |
| E | 0.75 | 0.80 | 0.85 |
| e | 0.40 BSC | | |
| H | 1.15 | 1.20 | 1.25 |
| L | 0.29 REF | | |
| L2 | 0.15 | 0.20 | 0.25 |




TOP VIEW



SIDE VIEW




BOTTOM VIEW



RECOMMENDED MOUNTING
FOOTPRINT

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**GENERIC**
**MARKING DIAGRAM***




XX = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. N/C
3. CATHODE

STYLE 3:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. GATE
2. SOURCE
3. DRAIN

| | | |
|---|---|---|
| **DOCUMENT NUMBER:** | **98AON12989D** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. |
| **DESCRIPTION:** | **SOT−723 1.20x0.80x0.50, 0.40P** | **PAGE 1 OF 1** |

**onsemi** and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

**TECHNICAL PUBLICATIONS**:
**Technical Library:** www.onsemi.com/design/resources/technical−documentation
**onsemi Website:** www.onsemi.com

**ONLINE SUPPORT**: www.onsemi.com/support
**For additional information, please contact your local Sales Representative at** www.onsemi.com/support/sales