# Complementary Bias Resistor Transistors R1 = 2.2 kΩ, R2 = 47 kΩ

## NPN and PNP Transistors with Monolithic Bias Resistor Network

# MUN5335DW1, NSBC123JPDXV6, NSBC123JPDP6

This series of digital transistors is designed to replace a single device and its external resistor bias network. The Bias Resistor Transistor (BRT) contains a single transistor with a monolithic bias network consisting of two resistors; a series base resistor and a base-emitter resistor. The BRT eliminates these individual components by integrating them into a single device. The use of a BRT can reduce both system cost and board space.

### Features

- Simplifies Circuit Design
- Reduces Board Space
- Reduces Component Count
- S and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable*
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant


### MAXIMUM RATINGS

($T_A$ = 25 °C both polarities $Q_1$ (PNP) & $Q_2$ (NPN), unless otherwise noted)

| Rating | Symbol | Max | Unit |
|---|---|---|---|
| Collector-Base Voltage | $V_{CBO}$ | 50 | Vdc |
| Collector-Emitter Voltage | $V_{CEO}$ | 50 | Vdc |
| Collector Current − Continuous | $I_C$ | 100 | mAdc |
| Input Forward Voltage | $V_{IN(fwd)}$ | 12 | Vdc |
| Input Reverse Voltage | $V_{IN(rev)}$ | 5 | Vdc |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


### PIN CONNECTIONS




### MARKING DIAGRAMS




**SOT-363**
**CASE 419B**







**SOT-563**
**CASE 463A**






**SOT-963**
**CASE 527AD**




35/D = Specific Device Code
M = Date Code*
▪ = Pb-Free Package

(Note: Microdot may be in either location)

* Date Code orientation may vary depending upon manufacturing location.

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 8 of this data sheet.

© Semiconductor Components Industries, LLC, 2016

## THERMAL CHARACTERISTICS

| Characteristic | | Symbol | Max | Unit |
|---|---|---|---|---|
| **MUN5335DW1 (SOT-363) ONE JUNCTION HEATED** | | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C<br>(Note 2)<br>Derate above 25 °C<br>(Note 2) | <br>(Note 1)<br><br>(Note 1)<br> | $P_D$ | <br>187<br>256<br>1.5<br>2.0 | <br>mW<br><br>mW/°C<br> |
| Thermal Resistance,<br>Junction to Ambient | (Note 1)<br>(Note 2) | $R_{\theta JA}$ | 670<br>490 | °C/W |
| **MUN5335DW1 (SOT-363) BOTH JUNCTION HEATED** (Note 3) | | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C<br>(Note 2)<br>Derate above 25 °C<br>(Note 2) | <br>(Note 1)<br><br>(Note 1)<br> | $P_D$ | <br>250<br>385<br>2.0<br>3.0 | <br>mW<br><br>mW/°C<br> |
| Thermal Resistance,<br>Junction to Ambient<br>(Note 2) | <br>(Note 1)<br> | $R_{\theta JA}$ | <br>493<br>325 | °C/W |
| Thermal Resistance,<br>Junction to Lead<br>(Note 2) | <br>(Note 1)<br> | $R_{\theta JL}$ | <br>188<br>208 | °C/W |
| Junction and Storage Temperature Range | | $T_J$, $T_{stg}$ | −55 to +150 | °C |
| **NSBC123JPDXV6 (SOT-563) ONE JUNCTION HEATED** | | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C<br>Derate above 25 °C | <br>(Note 1)<br>(Note 1) | $P_D$ | <br>357<br>2.9 | <br>mW<br>mW/°C |
| Thermal Resistance,<br>Junction to Ambient | <br>(Note 1) | $R_{\theta JA}$ | <br>350 | °C/W |
| **NSBC123JPDXV6 (SOT-563) BOTH JUNCTION HEATED** (Note 3) | | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C<br>Derate above 25 °C | <br>(Note 1)<br>(Note 1) | $P_D$ | <br>500<br>4.0 | <br>mW<br>mW/°C |
| Thermal Resistance,<br>Junction to Ambient | <br>(Note 1) | $R_{\theta JA}$ | <br>250 | °C/W |
| Junction and Storage Temperature Range | | $T_J$, $T_{stg}$ | −55 to +150 | °C |
| **NSBC123JPDP6 (SOT-963) ONE JUNCTION HEATED** | | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C<br>(Note 5)<br>Derate above 25 °C<br>(Note 5) | <br>(Note 4)<br><br>(Note 4)<br> | $P_D$ | <br>231<br>269<br>1.9<br>2.2 | <br>MW<br><br>mW/°C<br> |
| Thermal Resistance,<br>Junction to Ambient<br>(Note 5) | <br>(Note 4)<br> | $R_{\theta JA}$ | <br>540<br>464 | °C/W |
| **NSBC123JPDP6 (SOT-963) BOTH JUNCTION HEATED** (Note 3) | | | | |
| Total Device Dissipation<br>$T_A$ = 25 °C<br>(Note 5)<br>Derate above 25 °C<br>(Note 5) | <br>(Note 4)<br><br>(Note 4)<br> | $P_D$ | <br>339<br>408<br>2.7<br>3.3 | <br>MW<br><br>mW/°C<br> |
| Thermal Resistance,<br>Junction to Ambient<br>(Note 5) | <br>(Note 4)<br> | $R_{\theta JA}$ | <br>369<br>306 | °C/W |
| Junction and Storage Temperature Range | | $T_J$, $T_{stg}$ | −55 to +150 | °C |

1. FR-4 @ Minimum Pad.
2. FR-4 @ 1.0 × 1.0 Inch Pad.
3. Both junction heated values assume total power is sum of two equally powered channels.
4. FR-4 @ 100 $mm^2$, 1 oz. copper traces, still air.
5. FR-4 @ 500 $mm^2$, 1 oz. copper traces, still air.




Share Feedback
Your Opinion Matters

**ELECTRICAL CHARACTERISTICS** ($T_A$ = 25 °C both polarities $Q_1$ (PNP) & $Q_2$ (NPN), unless otherwise noted)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|---|---|---|---|---|---|
| **OFF CHARACTERISTICS** | | | | | |
| Collector-Base Cutoff Current ($V_{CB}$ = 50 V, $I_E$ = 0) | $I_{CBO}$ | – | – | 100 | nAdc |
| Collector-Emitter Cutoff Current ($V_{CE}$ = 50 V, $I_B$ = 0) | $I_{CEO}$ | – | – | 500 | nAdc |
| Emitter-Base Cutoff Current ($V_{EB}$ = 6.0 V, $I_C$ = 0) | $I_{EBO}$ | – | – | 0.2 | mAdc |
| Collector-Base Breakdown Voltage ($I_C$ = 10 μA, $I_E$ = 0) | $V_{(BR)CBO}$ | 50 | – | – | Vdc |
| Collector-Emitter Breakdown Voltage (Note 6) ($I_C$ = 2.0 mA, $I_B$ = 0) | $V_{(BR)CEO}$ | 50 | – | – | Vdc |
| **ON CHARACTERISTICS** | | | | | |
| DC Current Gain (Note 6) ($I_C$ = 5.0 mA, $V_{CE}$ = 10 V) | $h_{FE}$ | 80 | 140 | – | |
| Collector-Emitter Saturation Voltage (Note 6) ($I_C$ = 10 mA, $I_B$ = 0.3 mA) | $V_{CE(sat)}$ | – | – | 0.25 | V |
| Input Voltage (Off) ($V_{CE}$ = 5.0 V, $I_C$ = 100 μA) (NPN)<br>($V_{CE}$ = 5.0 V, $I_C$ = 100 μA) (PNP) | $V_{i(off)}$ | –<br>– | 0.6<br>0.6 | –<br>– | Vdc |
| Input Voltage (On) ($V_{CE}$ = 0.2 V, $I_C$ = 5.0 mA) (NPN)<br>($V_{CE}$ = 0.2 V, $I_C$ = 5.0 mA) (PNP) | $V_{i(on)}$ | –<br>– | 0.8<br>0.8 | –<br>– | Vdc |
| Output Voltage (On) ($V_{CC}$ = 5.0 V, $V_B$ = 2.5 V, $R_L$ = 1.0 kΩ) | $V_{OL}$ | – | – | 0.2 | Vdc |
| Output Voltage (Off) ($V_{CC}$ = 5.0 V, $V_B$ = 0.5 V, $R_L$ = 1.0 kΩ) | $V_{OH}$ | 4.9 | – | – | Vdc |
| Input Resistor | R1 | 1.5 | 2.2 | 2.9 | kΩ |
| Resistor Ratio | $R_1/R_2$ | 0.038 | 0.047 | 0.056 | |

6. Pulsed Condition: Pulse Width = 300 ms, Duty Cycle ≤ 2%.




(1) SOT-363; 1.0 × 1.0 Inch Pad
(2) SOT-563; Minimum Pad
(3) SOT-963; 100 $mm^2$, 1 oz. Copper Trace

**Figure 1. Derating Curve**



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS − NPN TRANSISTOR
## MUN5335DW1, NSBC123JPDXV6





**Figure 2. $V_{CE(sat)}$ vs. $I_C$**





**Figure 3. DC Current Gain**





**Figure 4. Output Capacitance**





**Figure 5. Output Current vs. Input Voltage**





**Figure 6. Input Voltage vs. Output Current**



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS − PNP TRANSISTOR
## MUN5335DW1, NSBC123JPDXV6





**Figure 7. $V_{CE(sat)}$ vs. $I_C$**





**Figure 8. DC Current Gain**





**Figure 9. Output Capacitance**





**Figure 10. Output Current vs. Input Voltage**





**Figure 11. Input Voltage vs. Output Current**



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS − NPN TRANSISTOR
## NSBC123JPDP6





**Figure 12. $V_{CE(sat)}$ vs. $I_C$**





**Figure 13. DC Current Gain**





**Figure 14. Output Capacitance**





**Figure 15. Output Current vs. Input Voltage**





**Figure 16. Input Voltage vs. Output Current**



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS − PNP TRANSISTOR
## NSBC123JPDP6





**Figure 17. $V_{CE(sat)}$ vs. $I_C$**





**Figure 18. DC Current Gain**





**Figure 19. Output Capacitance**





**Figure 20. Output Current vs. Input Voltage**





**Figure 21. Input Voltage vs. Output Current**



Share Feedback
Your Opinion Matters

## ORDERING INFORMATION

| Device | Marking | Package | Shipping† |
|---|---|---|---|
| MUN5335DW1T1G<br>MUN5335DW1T1G-NC<br>SMUN5335DW1T1G*<br>SMUN5335DW1T1G-NC* | 35 | SOT-363<br>(Pb-Free) | 3,000 / Tape & Reel |
| MUN5335DW1T2G<br>MUN5335DW1T2G-NC<br>SMUN5335DW1T2G*<br>SMUN5335DW1T2G-NC*” | | | |
| NSBC123JPDXV6T1G<br>NSBC123JPDXV6T1G-NC (Under Development)<br>NSVBC123JPDXV6T1G*<br>NSVBC123JPDXV6T1G-NC* (Under Development) | 35 | SOT-563<br>(Pb-Free) | 4,000 / Tape & Reel |
| NSBC123JPDP6T5G | D | SOT-963<br>(Pb-Free) | 8,000 / Tape & Reel |

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

* S, V and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.



Share Feedback
Your Opinion Matters

## REVISION HISTORY

| Revision | Description of Changes | Date |
|---|---|---|
| 5 | Rebranded the Data Sheet to **onsemi** format and marked the discontinued OPNs. | 6/26/2025 |
| 6 | Updated Ordering Information table. | 11/2/2026 |

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.




Share Feedback
Your Opinion Matters




**SC−88 2.00x1.25x0.90, 0.65P**
CASE 419B−02
ISSUE Z


DATE 18 APR 2024





TOP VIEW




SIDE VIEW




END VIEW





DETAIL A
SCALE 2:1

NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5−2018.
2. ALL DIMENSION ARE IN MILLIMETERS.
3. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.20 PER END.
4. DIMENSIONS D AND E1 AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AND DATUM H.
5. DATUMS A AND B ARE DETERMINED AT DATUM H.
6. DIMENSIONS b AND c APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08 AND 0.15 FROM THE TIP.
7. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 TOTAL IN EXCESS OF DIMENSION b AT MAXIMUM MATERIAL CONDITION. THE DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT.


| | MILLIMETERS | | |
|---|---|---|---|
| DIM | MIN. | NOM. | MAX. |
| A | −−− | −−− | 1.10 |
| A1 | 0.00 | −−− | 0.10 |
| A2 | 0.70 | 0.90 | 1.00 |
| b | 0.15 | 0.20 | 0.25 |
| c | 0.08 | 0.15 | 0.22 |
| D | 2.00 BSC | | |
| E | 2.10 BSC | | |
| E1 | 1.25 BSC | | |
| e | 0.65 BSC | | |
| L | 0.26 | 0.36 | 0.46 |
| L2 | 0.15 BSC | | |
| aaa | 0.15 | | |
| bbb | 0.30 | | |
| ccc | 0.10 | | |
| ddd | 0.10 | | |




RECOMMENDED MOUNTING FOOTPRINT*

* FOR ADDITIONAL INFORMATION ON OUR Pb−FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ONSEMI SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

## GENERIC MARKING DIAGRAM*




XXX = Specific Device Code
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation and/or position may vary depending upon manufacturing location.

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

**STYLES ON PAGE 2**

| | | | |
|---|---|---|---|
| **DOCUMENT NUMBER:** | **98ASB42985B** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. | |
| **DESCRIPTION:** | **SC−88 2.00x1.25x0.90, 0.65P** | | **PAGE 1 OF 2** |

**onsemi** and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**SC−88 2.00x1.25x0.90, 0.65P**
CASE 419B−02
ISSUE Z

DATE 18 APR 2024

STYLE 1:
PIN 1. EMITTER 2
2. BASE 2
3. COLLECTOR 1
4. EMITTER 1
5. BASE 1
6. COLLECTOR 2

STYLE 2:
CANCELLED

STYLE 3:
CANCELLED

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. COLLECTOR
4. EMITTER
5. BASE
6. ANODE

STYLE 5:
PIN 1. ANODE
2. ANODE
3. COLLECTOR
4. EMITTER
5. BASE
6. CATHODE

STYLE 6:
PIN 1. ANODE 2
2. N/C
3. CATHODE 1
4. ANODE 1
5. N/C
6. CATHODE 2

STYLE 7:
PIN 1. SOURCE 2
2. DRAIN 2
3. GATE 1
4. SOURCE 1
5. DRAIN 1
6. GATE 2

STYLE 8:
CANCELLED

STYLE 9:
PIN 1. EMITTER 2
2. EMITTER 1
3. COLLECTOR 1
4. BASE 1
5. BASE 2
6. COLLECTOR 2

STYLE 10:
PIN 1. SOURCE 2
2. SOURCE 1
3. GATE 1
4. DRAIN 1
5. DRAIN 2
6. GATE 2

STYLE 11:
PIN 1. CATHODE 2
2. CATHODE 2
3. ANODE 1
4. CATHODE 1
5. CATHODE 1
6. ANODE 2

STYLE 12:
PIN 1. ANODE 2
2. ANODE 2
3. CATHODE 1
4. ANODE 1
5. ANODE 1
6. CATHODE 2

STYLE 13:
PIN 1. ANODE
2. N/C
3. COLLECTOR
4. EMITTER
5. BASE
6. CATHODE

STYLE 14:
PIN 1. VREF
2. GND
3. GND
4. IOUT
5. VEN
6. VCC

STYLE 15:
PIN 1. ANODE 1
2. ANODE 2
3. ANODE 3
4. CATHODE 3
5. CATHODE 2
6. CATHODE 1

STYLE 16:
PIN 1. BASE 1
2. EMITTER 2
3. COLLECTOR 2
4. BASE 2
5. EMITTER 1
6. COLLECTOR 1

STYLE 17:
PIN 1. BASE 1
2. EMITTER 1
3. COLLECTOR 2
4. BASE 2
5. EMITTER 2
6. COLLECTOR 1

STYLE 18:
PIN 1. VIN1
2. VCC
3. VOUT2
4. VIN2
5. GND
6. VOUT1

STYLE 19:
PIN 1. I OUT
2. GND
3. GND
4. V CC
5. V EN
6. V REF

STYLE 20:
PIN 1. COLLECTOR
2. COLLECTOR
3. BASE
4. EMITTER
5. COLLECTOR
6. COLLECTOR

STYLE 21:
PIN 1. ANODE 1
2. N/C
3. ANODE 2
4. CATHODE 2
5. N/C
6. CATHODE 1

STYLE 22:
PIN 1. D1 (i)
2. GND
3. D2 (i)
4. D2 (c)
5. VBUS
6. D1 (c)

STYLE 23:
PIN 1. Vn
2. CH1
3. Vp
4. N/C
5. CH2
6. N/C

STYLE 24:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. CATHODE
5. CATHODE
6. CATHODE

STYLE 25:
PIN 1. BASE 1
2. CATHODE
3. COLLECTOR 2
4. BASE 2
5. EMITTER
6. COLLECTOR 1

STYLE 26:
PIN 1. SOURCE 1
2. GATE 1
3. DRAIN 2
4. SOURCE 2
5. GATE 2
6. DRAIN 1

STYLE 27:
PIN 1. BASE 2
2. BASE 1
3. COLLECTOR 1
4. EMITTER 1
5. EMITTER 2
6. COLLECTOR 2

STYLE 28:
PIN 1. DRAIN
2. DRAIN
3. GATE
4. SOURCE
5. DRAIN
6. DRAIN

STYLE 29:
PIN 1. ANODE
2. ANODE
3. COLLECTOR
4. EMITTER
5. BASE/ANODE
6. CATHODE


STYLE 30:
PIN 1. SOURCE 1
2. DRAIN 2
3. DRAIN 2
4. SOURCE 2
5. GATE 1
6. DRAIN 1

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

| | | | |
|---|---|---|---|
| **DOCUMENT NUMBER:** | **98ASB42985B** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. | |
| **DESCRIPTION:** | **SC−88 2.00x1.25x0.90, 0.65P** | | **PAGE 2 OF 2** |

**onsemi** and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.


© Semiconductor Components Industries, LLC, 2019




**SOT−563−6 1.60x1.20x0.55, 0.50P**
CASE 463A
ISSUE J

DATE 15 FEB 2024

NOTES:
1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5−2018.
2. ALL DIMENSION ARE IN MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.




TOP VIEW



SIDE VIEW

| DIM | MILLIMETERS | | |
|---|---|---|---|
| | MIN. | NOM. | MAX. |
| A | 0.50 | 0.55 | 0.60 |
| b | 0.17 | 0.22 | 0.27 |
| c | 0.08 | 0.13 | 0.18 |
| D | 1.50 | 1.60 | 1.70 |
| E | 1.10 | 1.20 | 1.30 |
| e | 0.50 BSC | | |
| H | 1.50 | 1.60 | 1.70 |
| L | 0.10 | 0.20 | 0.30 |



RECOMMENDED MOUNTING FOOTPRINT*

* FOR ADDITIONAL INFORMATION ON OUR Pb−FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

STYLE 1:
PIN 1. EMITTER 1
2. BASE 1
3. COLLECTOR 2
4. EMITTER 2
5. BASE 2
6. COLLECTOR 1

STYLE 2:
PIN 1. EMITTER 1
2. EMITTER 2
3. BASE 2
4. COLLECTOR 2
5. BASE 1
6. COLLECTOR 1

STYLE 3:
PIN 1. CATHODE 1
2. CATHODE 1
3. ANODE/ANODE 2
4. CATHODE 2
5. CATHODE 2
6. ANODE/ANODE 1

STYLE 4:
PIN 1. COLLECTOR
2. COLLECTOR
3. BASE
4. EMITTER
5. COLLECTOR
6. COLLECTOR

STYLE 5:
PIN 1. CATHODE
2. CATHODE
3. ANODE
4. ANODE
5. CATHODE
6. CATHODE

STYLE 6:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. CATHODE
5. CATHODE
6. CATHODE

STYLE 7:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. CATHODE
5. ANODE
6. CATHODE


STYLE 8:
PIN 1. DRAIN
2. DRAIN
3. GATE
4. SOURCE
5. DRAIN
6. DRAIN

STYLE 9:
PIN 1. SOURCE 1
2. GATE 1
3. DRAIN 2
4. SOURCE 2
5. GATE 2
6. DRAIN 1

STYLE 10:
PIN 1. CATHODE 1
2. N/C
3. CATHODE 2
4. ANODE 2
5. N/C
6. ANODE 1

STYLE 11:
PIN 1. EMITTER 2
2. BASE 2
3. COLLECTOR 1
4. EMITTER 1
5. BASE 1
6. COLLECTOR 2

**GENERIC MARKING DIAGRAM***





XX = Specific Device Code
M = Month Code
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

| | | | |
|---|---|---|---|
| **DOCUMENT NUMBER:** | **98AON11126D** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. | |
| **DESCRIPTION:** | **SOT−563−6 1.60x1.20x0.55, 0.50P** | | **PAGE 1 OF 1** |

**onsemi** and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.





**SOT−963 1.00x1.00x0.37, 0.35P**
CASE 527AD
ISSUE F

DATE 20 FEB 2024

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | MILLIMETERS | | |
|---|---|---|---|
| | MIN. | NOM. | MAX. |
| A | 0.34 | 0.37 | 0.40 |
| b | 0.10 | 0.15 | 0.20 |
| c | 0.07 | 0.12 | 0.17 |
| D | 0.95 | 1.00 | 1.05 |
| E | 0.75 | 0.80 | 0.85 |
| e | 0.35 BSC | | |
| H | 0.95 | 1.00 | 1.05 |
| L | 0.19 REF | | |
| L2 | 0.05 | 0.10 | 0.15 |




*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference manual, SOLDERRM/D.

STYLE 1:
PIN 1. EMITTER 1
2. BASE 1
3. COLLECTOR 2
4. EMITTER 2
5. BASE 2
6. COLLECTOR 1

STYLE 2:
PIN 1. EMITTER 1
2. EMITTER2
3. BASE 2
4. COLLECTOR 2
5. BASE 1
6. COLLECTOR 1

STYLE 3:
PIN 1. CATHODE 1
2. CATHODE 1
3. ANODE/ANODE 2
4. CATHODE 2
5. CATHODE 2
6. ANODE/ANODE 1

STYLE 4:
PIN 1. COLLECTOR
2. COLLECTOR
3. BASE
4. EMITTER
5. COLLECTOR
6. COLLECTOR

STYLE 5:
PIN 1. CATHODE
2. CATHODE
3. ANODE
4. ANODE
5. CATHODE
6. CATHODE

STYLE 6:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. CATHODE
5. CATHODE
6. CATHODE


STYLE 7:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. CATHODE
5. ANODE
6. CATHODE

STYLE 8:
PIN 1. DRAIN
2. DRAIN
3. GATE
4. SOURCE
5. DRAIN
6. DRAIN

STYLE 9:
PIN 1. SOURCE 1
2. GATE 1
3. DRAIN 2
4. SOURCE 2
5. GATE 2
6. DRAIN 1

STYLE 10:
PIN 1. CATHODE 1
2. N/C
3. CATHODE 2
4. ANODE 2
5. N/C
6. ANODE 1

**GENERIC MARKING DIAGRAM***




XX = Specific Device Code
M = Month Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

| | | |
|---|---|---|
| **DOCUMENT NUMBER:** | **98AON26456D** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. |
| **DESCRIPTION:** | **SOT−963 1.00x1.00x0.37, 0.35P** | **PAGE 1 OF 1** |

**onsemi** and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

**TECHNICAL PUBLICATIONS**:
**Technical Library:** www.onsemi.com/design/resources/technical−documentation
**onsemi Website:** www.onsemi.com

**ONLINE SUPPORT**: www.onsemi.com/support
**For additional information, please contact your local Sales Representative at** www.onsemi.com/support/sales